





## STEAMER

The Steam EP is the most commercially-evolved espresso machine in the industry. Designed for fluid, simple operation by the barista while maintaining high-end extraction capability. Design that you have come to expect, this Slayer machine is meant for every user and budget type. From a multi-cafe retailers, roaster or distributor, stepping up to Slayer and into an EP has never been easier.

# Classic 9-bar Extraction with Pre-Wet Control

Volumetric brewing with programmable pre-wet from 0-4 seconds.

#### **Push Button Actuation**

For fast programming and easy operation.

### **Four Volumetric Settings Per Group**

Each button can be programmed to hold two volumetric presets, four settings per group.

### Individual Brew Tanks with PID Temperature Control

Consistent and reliable performance, ideal for high-volume beverage service.

# Centralized, Heads-up Barista Dashboard

Easy to operate and program volumetrics, temperature, pre-wet and more.

### Password Protection of Deeper Programming

Give appropriate levels of control to baristas.

### **Unique Design**

Soft-Touch™ handles, powder coated wings and anodized aluminum panels.



#### **Essential Features**

- Volumetric activation, two buttons with four programmable settings
- Programmable HOLD 0-4 Seconds to pause water delivery before full pressure extraction.
- Programmable Pre-Wet 0-4 sec
- Centralized heads-up Barista Dashboard™
- Intuitive, password-protected menus
- Soft-Touch™ steam actuators and portafilters
- PID-controlled independent brew tanks
- · Hot water mix valve
- Massive work surface
- Wing channels keep wires and hoses hidden
- · Anodized aluminum finish, body color
- Powder coated matte black wings

### Specifications (2-group | 3-group)

- Width: 34 | 43.5 inches / 86.5 | 110.5 centimeters
- Length: 27.75 | 27.75 inches / 70.5 | 70.5 centimeters
- Height: 16.75 | 16.75 inches / 42.5 | 42.5 centimeters
- Weight: 220 | 305 pounds / 100 | 139 kilograms (tanks filled)
- Brew tanks: 1.7 liters, 600 watts
- Steam tank: 7.4 | 12 liters, 3,500 | 4500 watts
- Single-phase power: 220-240V, 50/60 hertz, 4.7 - 5.6 kW | 6.3 - 7.5 kW
- Three-phase power (optional): 380-415V3N, 50/60 hertz, 4.9 - 5.7 kW | 5.8 - 6.5 kW
- Wattage: 4,700 | 6300 watts







